

TYPE 20-1-2**Power-Clamps®****Construction / Ausführungen:**

- "W1" Screw/Schraube M6 x 45, DIN 912, 8.8
Band 20mm/1mm, DIN 1623; St.12.03
White galvanized/Weiß galvanisiert (Cr3)
- "W5" Screw/Schraube M6 x 45, DIN 912, A4
Band 20mm/1mm, (1.4404)
(Acid and seawater resistant)
(Säure- und Meerwasserbeständig)

Part-Nr. Artikel No.	Min.Dia. mm	Max.Dia. mm	Qty/Stück per/pro Box/Karton	Weight/Gew. Box/Karton Kg
20-1-2-040	32	40	75	9,7
20-1-2-045	36	45	65	8,6
20-1-2-050	40	50	60	8,1
20-1-2-055	45	55	50	7,2
20-1-2-060	50	60	45	6,7
20-1-2-065	55	65	40	6,2
20-1-2-070	60	70	35	5,6
20-1-2-075	65	75	30	4,9
20-1-2-080	70	80	60	10,2
20-1-2-085	75	85	50	8,8
20-1-2-090	80	90	50	9,1
20-1-2-095	85	95	40	7,4
20-1-2-100	90	100	40	7,7
20-1-2-105	95	105	40	8,7
20-1-2-110	100	110	35	7,1
20-1-2-115	105	115	30	6,4
20-1-2-120	110	120	30	6,5
20-1-2-125	115	125	30	6,7
20-1-2-130	120	130	25	5,7
20-1-2-135	125	135	25	5,8
20-1-2-140	130	140	20	4,7
20-1-2-145	135	145	20	4,9
20-1-2-150	140	150	20	5,0
20-1-2-155	145	155	15	3,8
20-1-2-160	150	160	15	3,9
20-1-2-165	155	165	15	4,0
20-1-2-170	160	170	15	4,1
20-1-2-175	165	175	10	2,8
20-1-2-180	170	180	10	2,9
20-1-2-190	180	190	10	3,2

Place of delivery: ex works / Lieferung: Ab Werk

Delivery time: According to agreement / Lieferzeit: nach Vereinbarung

The reliable connection for hose and tube systems
Die sichere Verbindung für Schlauch- und Rohrsysteme

