



### Construction / Ausführungen:

Band and bridge have raised edges preventing «notch effect»  
Band und Brücke haben abgerundete Kanten.

“W1” Band & Trunnions / Bolzen - Steel 12.03 - DIN1623 30mm/2mm  
Screw / Schraube 8.8 - DIN 933 M10  
White galvanized/Weiß galvanisiert (Cr3)

“W5” Band: Acid and seawater resistant steel (AISI 316) 30mm/2mm  
Band: Säure- und Meerwasserbeständiger Stahl(1.4404) 30/2mm  
Screw / Schraube - DIN 933 A4 / AISI 316 M10  
Trunnions - Stainless Steel (AISI 316)  
Bolzen - Stahl A4 (1.4404)

Part-Nr. Artikel No.	Min.Dia.	Max.Dia.
SD30-095	80	95
SD30-110	95	110
SD30-125	110	125
SD30-140	125	140
SD30-155	140	155
SD30-170	155	170
SD30-185	170	185
SD30-205	185	205
SD30-225	205	225
SD30-245	225	245
SD30-265	245	265
SD30-285	265	285
SD30-305	285	305
SD30-325	305	325
SD30-345	325	345
SD30-365	345	365
SD30-385	365	385
SD30-405	385	405
SD30-425	405	425
SD30-445	425	445
SD30-465	445	465

Place of delivery: ex works / Lieferung: Ab Werk  
Time of delivery: per Agreement / Lieferzeit: nach Vereinbarung



Subject to changes/Änderungen vorbehalten

The reliable connection for hose and tube systems  
Die sichere Verbindung für Schlauch- und Rohrsysteme